



BRIDGE INTERFACE [DISCONTINUED]

[Home](#) » [Products](#) » [Bridge Interface](#)

PRODUCT DESCRIPTION

The Green-GO Bridge Interface is intended to connect remote locations to a Green-GO network.

The Bridge Interface can support 2 connections in any of the 2 modes.

A connection in 'Bridge' mode will connect two Green-GO networks together via a separate network or internet. The Audio and optionally call signals will be transported from one Green-GO network to the other. This will then create one group spread over two sites. The group ID and name do not need to be the same on both sides.

A connection in 'Remote User' mode, simply becomes another user in the remote system.

There is also an iOS app available which transforms your iOS device into a beltpack! Instead of connecting to a remote Green-GO network, you can also connect to the iOS device.

Article number: GGO-BRIDGE

FEATURES

Serves up to 2 remote connections

Powered via PoE (802.3af-2003 Standard) or separate DC power supply

iOS App

DOWNLOADS

Firmware

□ 4a44

Software

□ Green-GO Control

□ Green-GO Update Connection

Please ask us any questions you have, and we'll gladly answer them

CONTACT US □

□ Home

□ News & Stories

□ Products

□ Downloads

□ Contact Us

□ Beltpacks

□ Multi-Channel Stations


□ Interfaces

□ Wall Panels

□ Switches

□ Accessories

□ Software



© 2018 Green-GO Digital