

# Beltpack

## Product ref: GBP2

### 2-channel Green-GO communications beltpack outstation

The Green-GO beltpack provides direct access to 2 channels (which may be a single direct user or a group). A colour backlit LCD display button provides text information, cue signals, acknowledgement and call functions.

A rotary encoder acts as a master volume control, and when pressed, the encoder answers the latest audio source. Two push buttons provide instant access to the two channels. All matrix data is held within the beltpack, which is powered via the Ethernet network connection. Headphone/microphone set (not supplied) connects via a 4-pin XLR4 panel connector.



#### Features include:

- Operates with any other Green-GO beltpack or multichannel desk (no matrix required)
- Powered by Power Over Ethernet (suitable network power supply is needed e.g. Green-GO 5-port switch), no batteries required
- All interconnection routing data, system setup and preferences are held in local memory and updated via the network and is updated/replaced if a beltpack or a desk is changed or added to the network.
- Green-GO setup freeware may be downloaded from the Green-GO website

Dimensions	80 x 40 x 130mm, 390g
Power	Power over Ethernet
Connections	Neutrik RJ45 Ethercon, XLR4-pin (M) panel socket for headphone/microphone
Controls	Backlit LCD display/control pushbutton, 2 x direct access push buttons, rotary encoder/pushbutton for master volume and answer
Supplied	Green-GO Beltpack, operator leaflet
Related products	MCD: range of 4, 8, 12, 16, 24 and 32 channel multi-channel outstations GWM: range of three wall-panel style outstations GG2W, GG4W: 2- and 4-wire analogue to digital interfaces GG55: 5-port PoE Ethernet switch