

# Multi-channel Panel

Product ref: MCR12

12 channel rack-mounted Green-GO outstation



## Features include:

- Operates with any Green-GO outstation (no matrix required)
- Provides distributed audio, show relay and paging system features
- Front panel tilts upwards to improve viewing angle
- Two MCR12 units may be connected in master/slave mode for 24 channels
- Powered by Power over Ethernet or separate DC power supply
- Includes 2 Ethernet LAN sockets with 100MBit switch
- All interconnection routing data, system setup and preferences are held in local memory
- Free Green-GO setup software

The Green-GO

MCR12 multi-channel 19" rack mounted panel provides individual pushbutton direct access to 12 communication channels, and two units may be linked in master/slave mode for a 24 channel outstation. Each channel has two multi-colour pushbuttons for 'talk' and 'listen, call and cue'. Text displays for each channel give the outstation's name and volume level. Soft menu buttons control the main operational master features, and the panel has an integral loudspeaker and microphone XLR connector. Line in/out connections and routing are provided for show relay, distributed audio and paging announcements. An XLR3 stalk microphone socket and an XLR4 headset connector are provided on the front panel, and twin Ethernet ports with integral switch are at the rear.

Dimensions	19" rack, 2U (483 x 88 x 109mm) 2.2kg.
Power	Power over Ethernet, or optional external power supply
Connections	Front: mic input, dynamic or phantom powered (12V), headset connection XLR4 Rear: 2 Neutrik Ethercon RJ45 Ethernet, 1 line input (program in) and 1 line output on XLR3 (e.g. for stage announcements), USB connection, 2 switch contact in and 2 switch contact out on a sub D-9 connector.
Controls	2 RGB backlit buttons per channel for talk/indication and control, Oled display per 4 channels for level info and channel label, central control display with buttons, rotary encoder for volume and parameter setting, front panel speaker.
Supplied	Green-GO 12-channel panel, operator instructions
Related products	GB2: 2-channel belt-pack. GWP: wallmount cuelight station. GWP-HS: wallmount station for headset/mic. GWP-SP: wallmount station with integral mic and speaker. GG2W, GG4W: 2- and 4-wire analogue to digital interfaces. GGS5: 5-port PoE Ethernet switch

Green-GO is designed and manufactured in the Netherlands by ELC Lighting.

Worldwide sales: ANIMA Lighting Ltd, Stand 20, CH-1897 Le Bouveret

T: +4179 210 4613 [www.greengocom.com](http://www.greengocom.com) E&OE