

Miniature Fiber Optic 3G-SDI Digital Video Extender



"SMPTE-424M 3G-SDI"

"SMPTE-292M HD-SDI"

"SMPTE-259M SDI"

"DVB-ASI"

Descriptions

The OPTICIS 3G-SDI extender, SDIX-100 is a miniature, Fiber Optic 3G-SDI Digital Video Transport System, supporting the new 1080p, 3G-SDI format. The SDIX-100 is designed to transport one(1) channel SMPTE-424M 3G-SDI, SMPTE-292M HD-SDI or SMPTE-259M serial digital video signal over long distance through either single-mode or multi-mode fiber with the same model.

Due to the use of advanced digital fiber optic transmission technology, no user adjustments are required in the Mini 3G-SDI extender system, enabling quick setup and trouble-free operation. The SDIX-100 series can handle SDI, DVB-ASI, HD-SDI, 3G-SDI, and many other video formats. The power connector has a latch-locking mechanism, thus no power disruption due to miss-handling problem.


The SDIX-100 series comes with a rugged, standalone, miniature unit.

Key Features

- ♦ Supports up to 3G-SDI.
- ♦ Offers re-clocker included model SDIX-100C as an option.
- Extends up to 30km @3G.
- ♦ Transports Multi-rate HD-SDI Digital Video over 1 Fiber.
- Latch-Locking Power Connector.
- HD-SDI BNC input connector and ST terminated fiber optical connector.
- Supports embedded audio (such as embedded AES audio signal).
- ♦ Robust metal die-casting enclosure for harsh environment
- ♦ Certifications: CE / FCC

SDIX-100-T

SDI Source





Miniature Fiber Optic 3G SDI Digital Video Transport Systems


Digital Video

Signal Format	SMPTE-424M 3G-SDI	
	SMPTE-292M HD-SDI	
	SMPTE-259M SDI	
	and many others	
Input Connector	75 Ohm SDI BNC	
Data Rate	3 Gbps	
Signal Level	800mVp-p +/- 50mV	

Optical

Fiber Type	Single-	mode and Multi-mode
Number of Fibers		1
Output Connector	ST (Single	e-mode and Multi-mode)
Power Budget		Min. 11dB
Distance		30km @3G

Drawing Dimension[mm]







Physical

Dimension (WDH)	19.5 x 50.7 x 19.5 (mm)
Power Level	+5 VDC @ 1.5 A
Operating	0 ~ 50℃
Temperature	U ~ 50 C
Humidity	10 to 85% RH, non-condensing



фтісіѕ

OPTICIS HQ

Opticis Co., Ltd. # 16Fl, Kins Tower 8 Sungnam-daero, 331 beon-gil, Bundang-gu, Seongnam-si, Gyunggi-do, 463-844 South Korea

Te I: +82 (31) 719-8033 Fax: +82 (31) 719-8032 tosales@opticis.com